07510.N TIMED TAP FOR URINAL



GENERAL DATA

- Cold/hot timed water tap for urinal.
- Model for wall mounting and exposed installation.
- Opening with push button.
- Interchangeable cartridge that includes the timed mechanism.
- Robust construction in chromed brass.
- Timed to 7±3 seconds.
- Elements of subjection included.

TECHNICAL DATA

- Material: CW617N brass chrome body.
- Cartridge material: CW617N chrome-plated brass push button + plastic components in POM.
- Chrome under standard EN248.
- Cartridge thread dimensions: M 28 x 1.5 mm.
- Flow at 3 bar: 6 l/min.
- Operation time: 7±3 s.
- Tª maximum 85 ºC.
- Tª maximum recommended 60 ºC.
- Maximum pressure: 5 bar.
- Minimum pressure: 0.5 bar.
- Recommended pressure: 3 bar.
- Plastic particle filter included.

SUGGESTED TEXT FOR PRESCRIPTION

Cold/hot timed water tap for urinal NOFER 07510.N with push button for wall mounting. It assembles a self-closing cartridge timed to 7±3 s made in chrome plated brass plus plastic components in POM. The body is also made of chromed cast brass. Flow rate of 6 l/min with 3 bars of dynamic pressure. Includes filter and all accessories for installation. Dimensions: 67.5 mm height x 97.7 mm width. Manufactured by NOFER, S.L. – Avda. de la Fama, 118 - c.p: 08940 Cornellà de Llobregat - Barcelona. www.nofer.com.

NOFER, S.L., reserves the right to modify and / or rectify the products and specifications without prior notice
Dimensions: ±3%
VERSION 1.0 08/2019

TECHNICAL DRAWING

